

Mechanical Requirements

Input

Pressure Range (factory set)	3 to 15 psig (PTP 3/15) 3 to 30 psig (PTP 3/30) 0 to minus 7.5 psig (PTP 0/-7.5)
------------------------------	--

Connections

Wire Size	Up to one 14 gauge maximum
Terminal Type	Plug-in terminal strip, plugs on four (4) square 5 mm pins, captive screw with cage clamp in tin plated brass.
Pneumatic Fitting Type	Aluminum silver anodized manifold with brass barbed fitting for tubing connection
Pneumatic Tubing Size/Type	Supplied with plugged 1/8"-27 FNPT gauge port 1/4" O.D. nominal polyethylene

Dimensions

3.25" L x 2.185" W x 1.5" H

Weight

3 oz

Mounting

Furnished with a 3.25" length of 2.25" snap track (HWST003)

Additional Mounting Options:

Optional DIN Rail Mounting: Order DRC kit and DIN Rail compliant HWST031 snap track - specify when ordering.

Optional: Two (2) 24" sections of 3.25" snap track for multiple PTP mounting - specify HWST001 when ordering.

Environmental Requirements

Operating Temperature Range	32 to 120 deg F
Storage Temperature Range	-20 to 150 deg F
Operating Humidity Range	10 to 95% non-condensing

Specifications may change without notice to improve product performance.